LEGISLATURE OF NEBRASKA ONE HUNDRED SIXTH LEGISLATURE

FIRST SESSION

LEGISLATIVE BILL 733

Introduced by Kolowski, 31.

Read first time January 23, 2019

Committee: Government, Military and Veterans Affairs

- 1 A BILL FOR AN ACT relating to the Election Act; to amend sections 32-904
- and 32-907, Reissue Revised Statutes of Nebraska, and section
- 3 32-101, Revised Statutes Cumulative Supplement, 2018; to provide and
- 4 change requirements for polling places; to harmonize provisions; and
- 5 to repeal the original sections.
- 6 Be it enacted by the people of the State of Nebraska,

LB733 2019

1 Section 1. Section 32-101, Revised Statutes Cumulative Supplement,

- 2 2018, is amended to read:
- 3 32-101 Sections 32-101 to 32-1551 and section 4 of this act shall be
- 4 known and may be cited as the Election Act.
- 5 Sec. 2. Section 32-904, Reissue Revised Statutes of Nebraska, is
- 6 amended to read:
- 7 32-904 (1) The election commissioner or county clerk shall
- 8 designate the polling places for each precinct at which the registered
- 9 voters of the precinct will cast their votes. Polling places representing
- 10 different precincts may be combined at a single location when potential
- 11 sites cannot be found, contracts for utilizing polling sites cannot be
- obtained, or a potential site is not accessible to handicapped persons as
- 13 provided in section 32-907 and section 4 of this act.
- 14 (2) When combining polling places at a single site for an election
- 15 other than a special election, the election commissioner or county clerk
- 16 shall clearly separate the polling places from each other and maintain
- 17 separate receiving boards. When combining polling places at a single site
- 18 for a special election, the election commissioner or county clerk may
- 19 combine the polling places and receiving boards.
- 20 (3) Polling places shall not be changed between the statewide
- 21 primary and general elections unless the election commissioner or county
- 22 clerk has been authorized to make such change by the Secretary of State.
- 23 If changes are authorized, the election commissioner or county clerk
- 24 shall notify each state and local candidate affected by the change.
- 25 (4) Notwithstanding any other provision of the Election Act, the
- 26 Secretary of State may adopt and promulgate rules and regulations, with
- 27 the consent of the appropriate election commissioner or county clerk, for
- 28 the establishment of polling places which may be used for voting pursuant
- 29 to section 32-1041 for the twenty days preceding the day of election.
- 30 Such polling places shall be in addition to the office of the election
- 31 commissioner or county clerk and the polling places otherwise established

LB733 2019 LB733 2019

- 1 pursuant to this section.
- 2 Sec. 3. Section 32-907, Reissue Revised Statutes of Nebraska, is
- 3 amended to read:
- 4 32-907 All polling places shall be accessible to all registered
- 5 voters and shall be in compliance with the federal Americans with
- 6 Disabilities Act of 1990, as amended, and the federal Help America Vote
- 7 Act of 2002, as amended. All polling places shall be modified or
- 8 relocated to architecturally barrier-free buildings to provide
- 9 unobstructed access to such polling places by people with physical
- 10 limitations as required by section 4 of this act. At least one voting
- 11 booth shall be so constructed as to provide easy access for people with
- 12 limitations, and shall accommodate a wheelchair, and shall have a cover
- 13 to provide privacy. The modifications required by this section and
- 14 <u>section 4 of this act</u> may be of a temporary nature to provide such
- 15 unobstructed access only on election day.
- 16 Sec. 4. (1) All polling places shall meet the following
- 17 requirements:
- 18 (a) Parking:
- 19 <u>(i) At least one handicap-accessible space per twenty-five parking</u>
- 20 <u>spaces;</u>
- 21 (ii) At least one designated van-accessible space with signage with
- 22 the International Symbol of Accessibility and designated as van
- 23 <u>accessible;</u>
- 24 (iii) Designated van-accessible spaces shall be at least ninety-six
- 25 inches wide with a ninety-six-inch access aisle or one hundred thirty-two
- 26 <u>inches wide with a sixty-inch-wide access aisle;</u>
- 27 <u>(iv) Vertical clearance of at least ninety-eight inches for the</u>
- 28 vehicular route to the parking space, in the parking space and access
- 29 <u>aisle</u>, and along the vehicular route to the exit;
- 30 <u>(v) Designated accessible parking spaces and the access aisles</u>
- 31 serving them on a level surface, with slopes not exceeding a gradient of

- 1 1:48 in all directions;
- 2 (vi) Surfaces of the designated accessible parking spaces and access
- 3 aisles must be stable, firm, and slip resistant;
- 4 <u>(vii) The designated accessible parking spaces must be located on</u>
- 5 the shortest accessible route to the accessible entrance; and
- 6 (viii) Signs at the entrances to the parking area shall indicate
- 7 that someone is available to bring a ballot out if access to the polling
- 8 <u>location is challenging, with a telephone number to contact poll workers,</u>
- 9 and shall be posted, with visible lettering to exceed three inches
- 10 (seventy-five millimeters), plus one-eighth inch (three and two-tenths
- 11 <u>millimeters</u>) per foot (three hundred five millimeters) of viewing
- 12 <u>distance more than twenty-one feet (sixty-four hundred millimeters) from</u>
- 13 <u>accessible parking spaces;</u>
- 14 (b) Exterior route to accessible entrance:
- 15 (i) Route must be at least thirty-six inches wide;
- 16 (ii) Route must be free of abrupt changes in level that are greater
- 17 than one-half inch, including stairs;
- 18 <u>(iii) Route must be free of surface openings that are greater than</u>
- 19 <u>one-half inch, such as grates or holes in the pavement;</u>
- 20 (iv) Walking surfaces must be stable, firm, and slip resistant;
- 21 (v) Route must be free of wall-mounted objects that protrude more
- 22 than four inches into the path of travel and are between twenty-seven
- 23 inches and eighty inches high;
- (vi) Route must be free of post-mounted objects that protrude more
- 25 than twelve inches into the path of travel and are between twenty-seven
- 26 inches and eighty inches high;
- 27 <u>(vii) Objects that hang over the pedestrian route must be eighty</u>
- 28 <u>inches high or higher, including the underside of exterior stairs;</u>
- 29 <u>(viii) If the route crosses a curb, the curb ramp must be at least</u>
- 30 thirty-six inches wide with a slope gradient of no more than 1:12; and
- 31 (ix) Running slope of any part of the route must not be greater than

LB733 2019

- 1 a gradient of 1:20;
- 2 (c) Polling place entrances:
- 3 (i) The clear width of the door opening of one door or one active
- 4 leaf of a double door must be at least thirty-two inches;
- 5 (ii) All door opening hardware must be useable with one hand without
- 6 tight grasping, pinching, or twisting of the wrist;
- 7 (iii) On the pull side of the door, there must be at least eighteen
- 8 <u>inches of clearance provided to the side of the latch;</u>
- 9 (iv) The area in front of the door must be level, with slopes no
- 10 greater than a gradient of 1:48 in all directions;
- 11 <u>(v) If there are doors in a series, the distance between the two</u>
- 12 <u>hinged doors must be at least forty-eight inches plus the width of the</u>
- 13 <u>door swinging into the space;</u>
- 14 (vi) Must be able to open the interior door with no more than five
- 15 pounds of force;
- 16 (vii) Door thresholds must be no higher than one-half inch;
- 17 <u>(viii) Inaccessible entrances must have signage directing voters to</u>
- 18 the accessible entrance with visible lettering to exceed three inches
- 19 <u>(seventy-five millimeters)</u>, plus one-eighth inch (three and two-tenths
- 20 millimeters) per foot (three hundred five millimeters) of viewing
- 21 distance more than twenty-one feet (sixty-four hundred millimeters) from
- 22 accessible parking spaces; and
- 23 (ix) If voters are directed to an alternative accessible entrance,
- 24 such entrance must be kept unlocked during voting hours;
- 25 (d) Route from entrance into voting area:
- 26 (i) Route must be at least thirty-six inches wide;
- 27 <u>(ii) Route must be free of wall-mounted objects that protrude more</u>
- 28 than four inches into the path of travel and are between twenty-seven
- 29 <u>inches and eighty inches high;</u>
- 30 (iii) Route must be free of post-mounted objects that protrude more
- 31 than twelve inches into the path of travel and are between twenty-seven

LB733 2019

- 1 inches and eighty inches high;
- 2 (iv) Objects that hang over the pedestrian route must be eighty
- 3 inches high or higher, including the underside of exterior stairs;
- 4 (v) If the route crosses a curb, the curb ramp must be at least
- 5 thirty-six inches wide with a slope gradient of no more than 1:12;
- 6 (vi) Running slope of part of the route must not be greater than a
- 7 gradient of 1:20;
- 8 (vii) If the route to the voting area has stairs, a platform lift or
- 9 elevator must be provided; and
- 10 (viii) If there are doors between the entrance and voting area:
- 11 (A) The clear width of the door opening of one door or one active
- 12 <u>leaf of a double door must be at least thirty-two inches;</u>
- 13 (B) All door opening hardware must be useable with one hand without
- 14 tight grasping, pinching, or twisting of the wrist;
- 15 (C) On the pull side of the door, there must be at least eighteen
- inches of clearance provided to the side of the latch;
- 17 (D) The area in front of the door must be level, with slopes of no
- 18 greater than a gradient of 1:48 in all directions;
- 19 (E) If there are doors in a series, the distance between the two
- 20 <u>hinged doors must be at least forty-eight inches plus the width of the</u>
- 21 <u>door swinging into the space;</u>
- 22 (F) Must be able to open the interior door with no more than five
- 23 pounds of force; and
- 24 (G) Door thresholds must be no higher than one-half inch;
- 25 (e) Voting area:
- 26 (i) Walking surfaces must be stable, firm, and slip resistant;
- 27 <u>(ii) Route must be free of wall-mounted objects that protrude more</u>
- 28 than four inches into the path of travel and are between twenty-seven
- 29 <u>inches and eighty inches high;</u>
- 30 (iii) Route must be free of post-mounted objects that protrude more
- 31 than twelve inches into the path of travel and are between twenty-seven

LB733 2019 LB733 2019

- 1 inches and eighty inches high;
- 2 (iv) Objects that hang over the pedestrian route must be eighty
- 3 inches high or higher, including the underside of exterior stairs;
- 4 (v) If the route crosses a curb, the curb ramp must be at least
- 5 thirty-six inches wide with a slope gradient of no more than 1:12;
- 6 (vi) Running slope of part of the route must not be greater than a
- 7 gradient of 1:20;
- 8 <u>(vii) There must be enough room to provide a route at least thirty-</u>
- 9 six inches wide to the registration table and voting stations;
- 10 (viii) Any machine used for voting must be available at each polling
- 11 <u>location and must be turned on and accessible at all times;</u>
- 12 (ix) Any machine used for voting must be placed in a location that
- 13 <u>allows privacy or a barrier must be set up;</u>
- 14 (x) Must be enough room to provide a turning space in front of at
- 15 <u>least one voting station, such as a circle that is at least sixty inches</u>
- 16 in diameter;
- 17 (xi) Must be enough room to provide a turning space in front of at
- 18 least one accessible machine used for voting, such as a circle that is at
- 19 <u>least sixty inches in diameter;</u>
- 20 (xii) Sign indicating that assistance is available and the contact
- 21 number for any election protection advocates approved by the Secretary of
- 22 State that contact the Secretary of State's office at least thirty days
- 23 prior to election. Sign must be two inches (fifty-one millimeters), plus
- 24 one-eighth inch (three and two-tenths millimeters) per foot (three
- 25 hundred five millimeters) of viewing distance more than one hundred
- 26 eighty inches (forty-five hundred seventy millimeters); and
- 27 (xiii) Seating must be available along the line to the polls;
- 28 (f) Ramps:
- 29 (i) Any ramp slope must have a gradient of no more than 1:12;
- 30 (ii) Cross slope of ramp must have a gradient of 1:48 or less;
- 31 (iii) Rise height for a ramp must run thirty inches or less;

LB733 2019 LB733 2019

1 (iv) Ramp measures between handrails must be at least thirty-six

- 2 inches wide;
- 3 (v) Ramp must have a level landing that is at least sixty inches
- 4 long at the top and bottom of each ramp section;
- 5 <u>(vi) For every thirty inches of rise, a level landing at least sixty</u>
- 6 inches long must be provided;
- 7 (vii) If a ramp changes direction, there must be a level landing, at
- 8 <u>least sixty inches by sixty inches, provided where the ramp changes</u>
- 9 <u>direction;</u>
- 10 (viii) For every rise of the ramp greater than six inches, handrails
- 11 <u>must be provided that are between thirty-four inches and thirty-eight</u>
- 12 <u>inches above the ramp surface;</u>
- 13 (ix) If the rise of the ramp is greater than six inches, handrails
- 14 must be provided that are between thirty-four inches and thirty-eight
- 15 inches above the ramp surface; and
- 16 <u>(x) If the rise of the ramp is greater than six inches and the ramp</u>
- 17 <u>or landing has a vertical drop-off on either side of the ramp, edge</u>
- 18 <u>protection must be provided;</u>
- 19 <u>(g) Lifts:</u>
- 20 <u>(i) Must be operational;</u>
- 21 <u>(ii) Must be independently operable;</u>
- 22 (iii) Must have thirty inches by forty-eight inches of clear floor
- 23 space within the lift;
- 24 (iv) Must have controls that are no higher than forty-eight inches;
- (v) Must have controls that are useable with one hand without tight
- 26 grasping, pinching, or twisting; and
- 27 (vi) Clear width of the door opening or gate opening at the end of
- 28 the lift must be at least thirty-two inches. If a side door or gate is
- 29 provided, the clear opening width must be at least forty-two inches; and
- 30 <u>(h) Elevators:</u>
- 31 (i) Must have an elevator car door opening that is at least thirty-

- 1 six inches wide;
- 2 (ii) Must have space to maneuver within the elevator car. Car must
- 3 be at least fifty-one inches deep and sixty-eight inches wide, eighty
- 4 inches deep and fifty-four inches wide, or sixty inches deep and sixty
- 5 <u>inches wide;</u>
- 6 (iii) Must have hallway elevator call buttons that are forty-eight
- 7 inches high or lower;
- 8 (iv) Must have visible and audible signals in the hallway to
- 9 indicate the arrival and direction of the elevator car; and
- 10 (v) Must have visible and audible signals within the elevator car to
- 11 <u>indicate the position of the car.</u>
- 12 (2) The Secretary of State shall provide biennial training for the
- 13 election commissioners and county clerks to help ensure they are informed
- 14 <u>about current standards in accessibility. All poll workers shall receive</u>
- 15 training on accessibility between appointment and serving at an election.
- 16 Sec. 5. Original sections 32-904 and 32-907, Reissue Revised
- 17 Statutes of Nebraska, and section 32-101, Revised Statutes Cumulative
- 18 Supplement, 2018, are repealed.